MATERIAL SAFETY DATA SHEET

SECTION I PRODUCT DENTIFICATION

SUPPLIER EVCOR SOLUTIONS INC.

TORONTO, ONTARIO M5V 1T5

TELEPHONE 800-860-1537 FAX 800-831-5104

CANUTEC (613) 966-6666

PRODUCT NAME SLICK RED

PRODUCT USE LUBRICATING GREASE

SECTION II HAZARDOUS INGREDIENTS

HAZARDOUS- APPROX- CAS NO. LD (50) LC(50) INGREDIENTS CONC. LD (50) LC(50)

 Aluminium Benzoate
 5-10
 7632-00-0
 ND
 ND

 MINERAL OIL
 35
 64742-52-5
 ND
 ND

SECTION III PHYSICAL DATA

PHYSICAL STATE RED SEMI-SOLID GREASE

ODOUR AND APPEARANCE PETROLEUM ODOR NLGI GRADE 2 GREASE

ODOUR THRESHOLD NA
SPECIFIC GRAVITY 0.92
VAPOUR PRESSURE NA
VAPOUR DENSITY(air=1) NA

EVAPORATION RATE 0.10 (Bu Ac =1)
SOLUBILITY IN WATER NEGLIBLE
BOILING POINT 700 DEG F
Ph NA
COEFF. WATER/OIL DISTR NA

SECTION IV FIRE AND EXPLOSION DATA

CONDITIONS OF FLAMMABILITY NONE

EXTINGUISHING MEDIA WATER FOG, FOAM, CO2 HAZARDOUS COMBUSTION PRODUCTS OXIDES OF CARBON

SPECIAL PROCEDURES SAME AS SURROUNDING MATERIAL

FLASH POINT (DEG)F 430
UPPER FLAMMABLE LIMIT NA
LOWER FLAMMABLE LIMIT NA
AUTO IGNITION TEMP NA
EXPLOSION DATA NA
SENSITIVITY TO STATIC CHARGE NA

SECTION V REACTIVITY DATA

CHEMICAL STABILITY NORMALLY STABLE

CONDITIONS TO AVOID EXTREME HEAT AND COLD

INCOMPATIBLE SUBSTANCES NONE

HAZARDOUS DECOMPOSITION CARBON DIOXIDE, CARBON MONOXIDE

HAZARDOUS POLYMERIZATION WILL NOT OCCUR

SECTION VI TOXICOLOGICAL PROPERTIES

ROUTE OF ENTRY

SKIN CONTACT NO
EYE CONTACT YES
INHALATION YES
INGESTION YES

SLICK RED

EFFECTS OF ACUTE EXPOSURE TO MATERIAL:

EYE CONTACT MAY CAUSE MILD IRRITATION; SKIN CONTACT MAY CAUSE DRYNESS OR DEFATTING; INHALATION MAY CAUSE IRRITATION OF NOSE, EYES AND THROAT; INGESTION MAY CAUSE IRRITATION OF MOUTH AND THROAT, NAUSEA AND VOMITING.

EFFECTS OF CHRONIC EXPOSURE: NE

EXPOSURE LIMITS OSHA 1988 5mg/Cu Meter for Mineral Oil

IRRITANCY OF MATERIAL NE SENSITIZATION TO MATERIAL NE

CARCINOGENICITY NONE KNOWN REPRODUCTIVE TOXICITY NONE KNOWN TERATOGENICITY NONE KNOWN MUTAGENICITY NONE KNOWN

SYNERGISTIC PRODUCTS NE

SECTION VII PREVENTIVE MEASURES

AND PROTECTION RUBBER OR VINYL

EYE PROTECTION GOGGLES IF EYE CONTACT POSSIBLE RESPIRATORY PROTECTION NORMAL VENTILATION ADEQUATE

FOOT WEAR NOT NORMALLY REQUIRED CLOTHING NORMAL CLOTHING ENGINEERING CONTROLS LOCAL EXHAUST

LEAK AND SPILL PROCEDURE STOP AND CONTAIN LEAK, PICK UP WITH

WET VACUUM, OR DILUTE WITH COPIOUS

AMOUNTS OF WATER.

WASTE DISPOSAL DISPOSE OF IN ACCORDANCE WITH LOCAL AND

MUNICIPAL BYLAWS.

HANDLING PROCEDURES & EQUIPMENT HANDLE WITH CARE AND SAFETY.

STORAGE REQUIREMENTS STORE AT AMBIENT TEMP. KEEP FROM

FREEZING.

SECTION VIII FIRST AID MEASURES

EYES: FLUSH WITH WATER FOR 15 MIN. IF IRRITATION PERSISTS, SEEK MEDICAL ATTENTION. SKIN: FLUSH WITH WATER AND APPLY A MOISTURE RESTORING LOTION TO SKIN IF IRRITATION

PERSISTS.

INHALATION: MOVE VICTIM TO FRESH AIR.

INGESTION: DO NOT INDUCE VOMITING, GIVE WATER, FOLLOWED BY SEVERAL GLASSES OF MILK IF AVAILABLE IF VOMITING OCCURS GIVE FLUIDS AND SEEK MEDICAL ATTENTION.

WHMIS CLASSIFICATION NOT A CONTROLLED SUBSTANCE UNDER W.H.M.I.S.

TDG CLASSIFICATION NR
PIN NR
PACKING GROUP NR

HAZARD RATING: HEALTH:1 FIRE:0 REACTIVITY:0 SPECIAL:

HAZARD RATING SCALE: 0=MINIMAL, 1=SLIGHT, 2=MODERATE, 3=SERIOUS, 4=SEVERE. NA=NOT

APPLICABLE, ND=NO DATA AVAILABLE, NE=NOT ESTABLISHED, NR NOT REGULATED.

DATE: January 1, 2015

DISCLAIMER: THE INFORMATION CONTAINED HEREIN IS COMPILED FROM SOURCES BELIEVED TO BE RELIABLE. THE MANNER AND CONDITIONS OF USE AND HANDLING MAY, INVOLVE OTHER AND ADDITIONAL CONSIDERATIONS. WE ACCEPT NO RESPONSIBILITY FOR THE ACCURACY, SUFFICIENCY, RELIABILITY OR FOR ANY LOSS OR INJURY RESULTING FROM THE USE OF THE INFORMATION.

SLICK RED